

Armadillo LED - Evolution In Lighting

Tel. 0845 060 4000 Intl. +44 1371 87 69 69
Fax. 0845 060 4001 Intl. +44 1371 87 54 37

Bigods Hall | Bigods Lane | Great Dunmow | Essex | CM6 3BE | England

email: sales@armark.com web: www.armadilloLED.com online: @armadilloled



LED FLAT PANEL

LUMEN FLUX >120LM/W
FREQUENCY WAVE FREE
5 YEAR WARRANTY
FIRE RATED



© 2014 Armadillo LED - Evolution In Lighting (part of Armadillo Marketing Limited est. 1996)
All rights reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.
No liability will be accepted by the publisher for any consequence of its use.

Key Features and Benefits:

Cornerstone of any lighting design and retrofit

FWF™ Frequency Wave Free technology (no ripple effect)

Fire proof tested - TP rated

(BS 2782-0:2004 Annex B method 508A:
Rate of burning test on LED Panel and UL-94)

IP67 Detachable power supply

IP54 Panel - easy clean - no maintenance

IP54 Screw Lock connection between panel and power supply

5 Year Warranty as standard

Optional Emergency 3hrs for complete panel (pre-wired plug and play)

Dimmable option (DALi, 1-10V)

LED Efficiency >120lm/W

Lamp Efficacy >100lm/W with CRI>80

Symmetrical ultra wide light distribution

LGP lens - high uniformity and no glare

Fit Standard Sizes from 300mm to 1200mm

Bespoke sizes available up to 1543mm

Only 12mm panel depth

Security suspension wires supplied optionally

Operating Temp: -25°C ~ 50°C


Product lifetime >60,000hrs

Power factor >0.92


IP67 LED Power Supply
FWF™ Wave Frequency Free
(no ripple effect)
technology as STANDARD.
Suitable for all applications.
screw fit IP54 Plug.



High performance efficacy,
LGP (Light Guide Pattern)
ensures great uniformity,
even symmetrical light
distribution, stable colour,
high CRI and no glare.




Four side edge Lit
with High Quality LED Light sources.
Sleek solid white coated aluminium frame.
Robust, design with no sharp edges



LED Panel Light - Recessed Mount, Suspended, Surface Mounted, Burgess Ceiling

LED Panel - Family



Optical specification:

Colour Temp. 4000K (Option: 5000K)
 Colour Render Index >80CRI (Option: Ra>90)
 Light Distribution Wide Beam - no glare
 Operating temp. -25°C ~ +50°C
 L70 hrs 60000hrs

Electrical Specification:

Input voltage: 120~277V 50/60Hz
 Power Factor: >0.92
 Dimming: (Option: 1-10V, DALI)

IP67 LED Power Supply FWF™ Wave Frequency Free


Components and materials:

LED Light source: SMD
 Power supply: ArmadilloLED FWF™ Series
 Housing: Aluminium frame white coated
 Heatsink: Extruded aluminium
 Optic Lens: PMMA LGP™
 IP rating: IP54 LED Panel; IP67 Power Supply

General specification

Product	Power	Dimensions: mm	Weight: kgs
PL3030	20W	295 x 295	1.20
PL3060	25W	295 x 595	2.00
PL6060	40W	595 x 595	4.20
PL1230	45W	1195 x 295	4.20
PL1260	80W	1195 x 595	7.80


Sizes available




Mounting options:

- Recessed** supplied as option with extra two suspension rods, allow attach panel to frame or ceiling for future maintenance.
- Suspended** 4 x suspended rods supplied, to be attached direct to panel frame.
- Surface Mount** frame supplied along with screws and plugs. Profile depth allow to fit power supply and optional emergency inside box, ensures clean and aesthetic installation.
- Burgess Clip In** Direct retrofit panel frame, combined with ArmadilloLED panel is an easy "fit and forget" package.

Light Distribution Curve



Wide light distribution means uniform light on wall ceiling and floors. Retrofit and new design may allow to reduce number of fittings overall. LGP™ - Light Guide Pattern technology, PMMA acrylic plate covered with printed pattern guarantee uniform distribution at the best possible brightness. Function is to distribute light from light source located at the edge over the entire surface. Light distribution consists of reflecting the light by the pattern printed on the PMMA acrylic plate. Four sided edge lit panel and LGP™ technology ensures high quality light and feel factor.



Surface Mount White Frame Box (Optional)



all sizes available