

Armadillo LED - Evolution In Lighting

Tel. 0845 060 4000 Intl. +44 1371 87 69 69  
Fax. 0845 060 4001 Intl. +44 1371 87 54 37

Bigods Hall | Bigods Lane | Great Dunmow | Essex | CM6 3BE | England

email: sales@armark.com web: www.armadilloLED.com online: @armadilloled



## Chameleon LED RGBW IP67 Lighting Flood projector



© 2014 Armadillo LED - Evolution In Lighting (part of Armadillo Marketing Limited est. 1996)  
All rights reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.  
No liability will be accepted by the publisher for any consequence of its use.



## Specifications

- **SOURCE**

- n. 7 RGBW/FC LEDs
  - Total out lumen: R 500lm, G 820lm, B 150lm, W 1050lm

- **OPTIC**

- 25° standard beam (32mm lenses)
  - On request: narrow, wide (32mm lenses)

- **TILT**

- Manual 360°

- **CONTROL**

- Standard interface: RS-485
  - Protocol: USITT DMX 512

- **CONNECTIONS**

- Signal: XRL 5pin (on request 3pin) male-female connector
  - Main Power: 3x1mm cable

- **SETUP AND CONFIGURATION**

- Remote configuration by DRS Setup device
  - Dedicated DMX channel for white balance
  - DMX or automatic mode with MASTER/SLAVE function
  - Intelligent temperature control
  - Flicker free function
  - Smooth dimming function
  - Halogen simulation
  - CYM emulation

- **SAFETY**

- eyebolts for safety chain

- **IP 67 RATING PROTECTION**

- **POWER SUPPLY**

- Voltage range: 100-240VAC

- Frequency range: 47-63Hz

- Active Power factor:

- PF>0.91/230VAC, PF>0.98/120VAC

- Current: 0.22A@230VAC, 0.38A@120V

- Power: 45W

- **DMX CHANNELS**

- 9 ch mode

- 5 ch mode

- 4 ch mode

- **PHYSICAL**

- WxDxH: 185x140x230mm

- Weight: 2 Kg.

Dimensions & Drawings

