


Armadillo LED - Evolution In Lighting

Tel. 0845 060 4000 Intl. +44 1371 87 69 69
Fax. 0845 060 4001 Intl. +44 1371 87 54 37

Bigods Hall | Bigods Lane | Great Dunmow | Essex | CM6 3BE | England

email: sales@armark.com web: www.armadilloLED.com online: @armadilloled

QuadraLED Magnalock™ Permanent Magnetic Seal IP65 Security Glass LED



© 2014 Armadillo LED - Evolution In Lighting (part of Armadillo Marketing Limited est. 1996)
All rights reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.
No liability will be accepted by the publisher for any consequence of its use.



QuadraLED Magnalock™

The QuadraLED Magnalock™ luminaire is designed for mounting in extra demanding areas. Equipped with a security glass cover, tightly sealed by multiple high power permanent neodymium magnets to ensure IP65 protection, and easy maintenance. Standard fit into a traditional 600mm x 600mm grid ceiling, surface mounting and various other fitting sizes available. High performance LED modules provide excellent light levels with high colour render of CRI >90 to reveal the true colours of surroundings. Various colour temperatures are available from 3000k up to 5000k. Other options include 1-10v or DALI dimming, and emergency power packs.

QuadraLED Magnalock™ Recessed/Surface
Mount Glass 600mm x 600mm



Colour Temperature	4000K (Optional: 3000k, 5000K)	Warranty	5 Years
Colour Rendering Index	CRI >90	Efficiency	>105lm/w
Wattage	40W or 65W	Optional Dimming	1-10V, DALI
Lifetime	50,000 Hours	Optional Emergency	Yes
IP Rating	IP65		
Voltage	AC100-277V 50/60Hz		

QUAD-MAG-RECD-6X6-40	Recess Mounted Glass LED Panel IP65 ACTUAL SIZE 598mm x 598mm 40W
QUAD-MAG-RECD-6X6-65	Recess Mounted Glass LED Panel IP65 ACTUAL SIZE 598mm x 598mm 65W

QUAD-MAG-SURF-6X6-40	Surface Mounted Glass LED Panel IP65 ACTUAL SIZE 598mm x 598mm 40W
QUAD-MAG-SURF-6X6-65	Surface Mounted Glass LED Panel IP65 ACTUAL SIZE 598mm x 598mm 65W

QuadraLED Magnalock™ Recessed/Surface
Mount Glass 300mm x 1200mm




Colour Temperature	4000K (Optional: 3000k, 5000K)	Warranty	5 Years
Colour Rendering Index	CRI >90	Efficiency	>105lm/w
Wattage	40W or 65W	Optional Dimming	1-10V, DALI
Lifetime	50,000 Hours	Optional Emergency	Yes
IP Rating	IP65		
Voltage	AC100-277V 50/60Hz		

QUAD-MAG-RECD-12X3-40	Recessed Mounted Glass LED Panel IP65 ACTUAL SIZE 1198mm x 298mm 40W
QUAD-MAG-RECD-12X3-65	Recessed Mounted Glass LED Panel IP65 ACTUAL SIZE 1198mm x 298mm 65W

QUAD-MAG-SURF-12X3-40	Surface Mounted Glass LED Panel IP65 ACTUAL SIZE 1198mm x 298mm 40W
QUAD-MAG-SURF-12X3-65	Surface Mounted Glass LED Panel IP65 ACTUAL SIZE 1198mm x 298mm 65W


QuadraLED Magnalock™ Features




Multiple modules for easy replacement and upgrades. High CRI >90 to reveal the true colours of surroundings. Excellent 105lm/w with full control options of DALI, 1-10v as specified or required.



Toughened security glass tightly sealed to IP65, safety cables inside for easy maintenance and inspection.



Easy to use unique tool to remove the security glass safely. To put back, simply place the glass covers back on and watch it lock securely into place.



'Magnalock™' Technology - Multiple high power permanent neodymium magnets lock the glass cover in place and ensure a tight seal for IP65 ingress protection against water and dust.