


ARMARK SP-FL RANGE

SPORT & STADIUM LED LIGHTING

PRODUCT SPECIFICATION SHEET



SP-FL 100W-200W - SMALL HOUSING



FEATURES:

- Latest LED chipset technology achieving up to 160lm/W
- Latest low glare PVD Reflector technology
- 100W-200W LEDs to replace equivalent of 250W-500W metal halide lamps
- Outstanding saving compared to metal halide lamps
- Easy Maintenance
- 7 year Warranty

SPECIFICATIONS:



- Indoor Sports lighting
- Outdoor Sports lighting
- Area Sports lighting
- General Sports floodlighting
- IP Rating: IP65
- Housing: Marine grade aluminium
- Installation height: Up to 30m
- Chlorine Protection System
- Max Windage Area (m) = 0.488
- Max SCx Values by Side (m) = 0.108
- Total Weight: 10.5 kg

ELECTRICAL SPECIFICATION:


- Input Voltage: 90-305V or 180-528V, 50/60Hz Class 1 Drivers
- Nominal Voltage: 100-265V 50-60Hz
- Power Factor: >0.9 at full load
- Total Harmonic Distortion: < 20% at full load
- Integral 10 kV surge protection as standard
- Electrical Class: III(**)
- Wattages: 100W-200W

PRODUCT DETAILS:

MODEL NUMBER	RATED POWER	INPUT VOLTAGE	LED	DRIVER	LUMINOUS FLUX	CCT	CRI	LIFE TIME	OPERATING TEMP.
SP-FL-100	100W	90-305VAC/180-528VAC	Nichia	Meanwell	16.000lm	2700-7000K	80	50.000hrs	-40-70°
SP-FL-150	150W	90-305VAC/180-528VAC	Nichia	Meanwell	24.000lm	2700-7000K	80	50.000hrs	-40-70°
SP-FL-200	200W	90-305VAC/180-528VAC	Nichia	Meanwell	32.000lm	2700-7000K	80	50.000hrs	-40-70°



SP-FL 300W-400W - MEDIUM HOUSING



FEATURES:

- Latest LED chipset technology achieving up to 160lm/W
- Latest low glare PVD Reflector technology
- 300W-400W LEDs to replace equivalent of 750W-1000W metal halide lamps
- Outstanding saving compared to metal halide lamps
- Easy Maintenance
- 7 year Warranty

SPECIFICATIONS:


- Indoor Sports lighting
- Outdoor Sports lighting
- Area Sports lighting
- General Sports floodlighting
- IP Rating: IP65
- Housing: Marine grade aluminium
- Installation height: Up to 30m
- Chlorine Protection System
- Max Windage Area (m) = 0.318
- Max SCx Values by Side (m) = 0.07
- Total Weight: 19.5 kg

ELECTRICAL SPECIFICATION:


- Input Voltage: 90-305V or 180-528V, 50/60Hz Class 1 Drivers
- Nominal Voltage: 100-265V 50-60Hz
- Power Factor: >0.9 at full load
- Total Harmonic Distortion: < 20% at full load
- Integral 10 kV surge protection as standard
- Electrical Class: III(**)
- Wattages: 300W-400W

PRODUCT DETAILS:

MODEL NUMBER	RATED POWER	INPUT VOLTAGE	LED	DRIVER	LUMINOUS FLUX	CCT	CRI	LIFE TIME	OPERATING TEMP.
SP-FL-300	300W	90-305VAC/I 80-528VAC	Nichia	Meanwell	48.000lm	2700-7000K	80	50.000hrs	-40-70°
SP-FL-400	400W	90-305VAC/180-528VAC	Nichia	Meanwell	64.000lm	2700-7000K	80	50.000hrs	-40-70°



SP-FL 500W-800W - LARGE HOUSING



FEATURES:

- Latest LED chipset technology achieving up to 160lm/W
- Latest low glare PVD Reflector technology
- 500W-800W LEDs to replace equivalent of 1000W-1500W metal halide lamps
- Outstanding saving compared to metal halide lamps
- Easy Maintenance
- 7 year Warranty

SPECIFICATIONS:

- Outdoor Sports lighting
- High Mast Sports lighting
- Area Sports lighting
- General Sports floodlighting
- IP Rating: IP65
- Housing: Marine grade alluminium
- Instalattion height: Up to 30m
- Chlorine Protection System
- Max Windage Area (m) = 0.167
- Max SCx Values by Side (m) = 0.039
- Total Weight: 33.5 kg

ELECTRICAL SPECIFICATION:

- Input Voltage: 90-305V or 180-528V, 50/60Hz Class 1 Drivers
- Nominal Voltage: 90-305V 50- 60Hz
- Power Factor: >0.9 at full load
- Total Harmonic Distortion: < 20% at full load
- Integral 10 kV surge protection as standard
- Electrical Class: III(**)
- Wattages: 500W-800W

PRODUCT DETAILS:

MODEL NUMBER	RATED POWER	INPUT VOLTAGE	LED	DRIVER	LUMINOUS FLUX	CCT	CRI	LIFE TIME	OPERATING TEMP.
SP-FL-500	500W	90-305VAC/180-528VAC	Nichia	Meanwell	80.000lm	2700-7000K	80	50.000hrs	-40-70°
SP-FL-600	600W	90-305VAC/180-528VAC	Nichia	Meanwell	96.000lm	2700-7000K	80	50.000hrs	-40-70°
SP-FL-800	800W	90-305VAC/180-528VAC	Nichia	Meanwell	128.000lm	2700-7000K	80	50.000hrs	-40-70°